

**Section 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Product name:** 206 CERAMIC HTA FLUID ACTIVATOR

**Product code:** 206

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet**

**Company name:** Resimac Limited  
Unit B, Park Barn Estate  
Station Road  
Topcliffe, Thirsk  
North Yorkshire  
YO7 3SE  
United Kingdom

**Tel:** 01845 577498

**Email:** info@resimac.co.uk

**1.4. Emergency telephone number**

**Emergency tel:** 01845 577498

**Section 2: Hazards identification****2.1. Classification of the substance or mixture**

**Classification under CLP:** Acute Tox. 4: H302+332; Carc. 2: H351; Repr. 2: H361f; Skin Corr. 1B: H314; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335

**Most important adverse effects:** Harmful if swallowed or if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.

**2.2. Label elements****Label elements:**

**Hazard statements:** H302+332: Harmful if swallowed or if inhaled.  
H314: Causes severe skin burns and eye damage.  
H317: May cause an allergic skin reaction.  
H335: May cause respiratory irritation.  
H351: Suspected of causing cancer.  
H361f: Suspected of damaging fertility.  
H373: May cause damage to organs through prolonged or repeated exposure.

[cont...]

**SAFETY DATA SHEET**  
206 CERAMIC HTA FLUID ACTIVATOR

Page: 2

**Signal words:** Danger

**Hazard pictograms:** GHS05: Corrosion

GHS07: Exclamation mark

GHS08: Health hazard



**Precautionary statements:** P102: Keep out of reach of children.  
P202: Do not handle until all safety precautions have been read and understood.  
P260: Do not breathe vapours.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314: Get medical advice/attention if you feel unwell.  
P501: Dispose of contents/container to hazardous or special waste collection point.

**2.3. Other hazards**

**PBT:** This product is not identified as a PBT/vPvB substance.

**Section 3: Composition/information on ingredients**

**3.2. Mixtures**

**Hazardous ingredients:**

1,2-CYCLOHEXANEDIAMINE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
211-776-7	694-83-7	-	Skin Corr. 1B: H314	50-70%

FURFURYL ALCOHOL

202-626-1	98-00-0	-	Carc. 2: H351; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335	10-30%
-----------	---------	---	--	--------

2,2'-IMINODIETHYLAMINE

203-865-4	111-40-0	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317	10-30%
-----------	----------	---	---	--------

[cont...]

**SAFETY DATA SHEET**  
206 CERAMIC HTA FLUID ACTIVATOR

Page: 3

4,4'-ISOPROPYLIDENEDIPHENOL

201-245-8	80-05-7	-	Repr. 2: H361f; STOT SE 3: H335; Eye Dam. 1: H318; Skin Sens. 1: H317	1-10%
-----------	---------	---	---	-------

#### Section 4: First aid measures

##### 4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

##### 4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
- Eye contact:** Corneal burns may occur. May cause permanent damage.
- Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.
- Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

##### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

#### Section 5: Fire-fighting measures

##### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

##### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Corrosive. In combustion emits toxic fumes.

[cont...]

**SAFETY DATA SHEET**  
206 CERAMIC HTA FLUID ACTIVATOR

Page: 4

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

[cont...]

**SAFETY DATA SHEET**  
206 CERAMIC HTA FLUID ACTIVATOR

Page: 5

**Hazardous ingredients:**

**FURFURYL ALCOHOL**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	20 mg/m3	61 mg/m3	-	-

**2,2'-IMINODIETHYLAMINE**

UK	4.3 mg/m3	-	-	-
----	-----------	---	---	---

**4,4'-ISOPROPYLIDENEDIPHENOL**

UK	5 mg/m3	5 mg/m3	-	-
----	---------	---------	---	---

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Amber

**Odour:** Ammoniacal

**Solubility in water:** Insoluble

**Viscosity:** Non-viscous

**Boiling point/range°C:** >35

**Flash point°C:** 60 - 93

**Autoflammability°C:** No data available.

**Relative density:** 1.0

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

[cont...]

**SAFETY DATA SHEET**  
206 CERAMIC HTA FLUID ACTIVATOR

Page: 6

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**1,2-CYCLOHEXANEDIAMINE**

ORAL	RAT	LD50	4556	mg/kg
------	-----	------	------	-------

**FURFURYL ALCOHOL**

ORL	MUS	LD50	338	mg/kg
ORL	RAT	LD50	460	mg/kg
SKN	RAT	LD50	3825	mg/kg

**2,2'-IMINODIETHYLAMINE**

IPR	RAT	LD50	74	mg/kg
ORL	MUS	LD50	970	mg/kg
ORL	RAT	LD50	970	mg/kg

**4,4'-ISOPROPYLIDENEDIPHENOL**

ORL	MUS	LD50	2400	mg/kg
ORL	RAT	LD50	3250	mg/kg

**Relevant hazards for substance:**

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated

[cont...]

**SAFETY DATA SHEET**  
206 CERAMIC HTA FLUID ACTIVATOR

Page: 7

Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

**Eye contact:** Corneal burns may occur. May cause permanent damage.

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** No data available.

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

**SAFETY DATA SHEET**  
206 CERAMIC HTA FLUID ACTIVATOR

Page: 8

**Section 14: Transport information**

**14.1. UN number**

UN number: UN2735

**14.2. UN proper shipping name**

Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.  
(1,2-CYCLOHEXANEDIAMINE)

**14.3. Transport hazard class(es)**

Transport class: 8

**14.4. Packing group**

Packing group: III

**14.5. Environmental hazards**

Environmentally hazardous: No

Marine pollutant: No

**14.6. Special precautions for user**

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Specific regulations: Not applicable.

**15.2. Chemical Safety Assessment**

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H302+332: Harmful if swallowed or if inhaled.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

[cont...]

**SAFETY DATA SHEET**  
206 CERAMIC HTA FLUID ACTIVATOR

**Page: 9**

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H361f: Suspected of damaging fertility.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.